

# PRODUCT DATA SHEET

## Sikadur<sup>®</sup>-505

Filler for the preparation of industrial coatings

### DESCRIPTION

Aggregate size 0.1 - 0.3 mm.

### USES

Non-skid surfacing for Sikafloor<sup>®</sup> self levelling flooring compound.

### CHARACTERISTICS / ADVANTAGES

System component of many Sikafloor<sup>®</sup> Structures.

### PRODUCT INFORMATION

Composition	Quarzsand
Packaging	25 kg/bag
Shelf life	The product does not expire if stored in undamaged, original, sealed packaging, and if the storage conditions are met.
Storage conditions	Sikadur <sup>®</sup> -505 shall be stored in cool and dry conditions at temperatures between +5 °C and +30 °C. Must be protected from direct sunlight, rain, snow and ice, etc.
Appearance and colour	Grey

### BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



### PRODUCT DATA SHEET

Sikadur®-505

March 2022, Version 02.02

020816010010000015

Sikadur-505-en-MN-(03-2022)-2-2.pdf